APPLICABLE STOCK NOS. 5680-9001-3, $1^{\frac{1}{2}}$ 5680-9002-1, 2 -SECTION TO BE GRAY IRON CASTING, ASTM A-48 CLASS NO. 35B -CASTING SHALL CONFORM TO AND BE MANUFACTURED IN ACCORDANCE WITH THE REQUIREMENTS OF AASHTO STD M306, LATEST REVISION NOMINAL В Α RISE 1 1/2" 1 1/2" 3-1/8" 2" 2" 3-1/8" DETAIL A SEE DETAIL A 25 3/4" 24" 23 3/4" 22" 23 1/2" 23 3/4" MACHINED SURFACE SECTION A-A ALL DIMENSION ARE IN INCHES UNLESS OTHERWISE SPECIFIED. TOLERANCES: ± 1/16" PROCUREMENT AND MANUFACTURING DETAIL **REVISIONS:** May 3, 2021 | 9:23 PM APPROVED: WASHINGTON 22-INCH NON-WATERTIGHT P&M**SUBURBAN** DocuSigned by: MANHOLE ADJUSTING RING, 6.0 **SANITARY** Jaime Garcia COMMISSION 1¹ AND 2" HEIGHT MATERIALS MANAGERER 3469034 P.O. MANAGER P&M6.0